

VFI[®]-Primers



VFI's family of primers have a broad variety of uses from general purpose primers to water based bonding primers. Our primers have been tested and proven by the toughest industrial conditions. They are formulated to adhere to a wide range of surfaces including; metal, single-ply, concrete, wood, mod bit and BUR.

VFI-PRIMER ADVANTAGES

- Excellent adhesion
- Easy application
- Superior weatherability
- Longer re-coat window
- Manufactured by Volatile Free, Inc.

VFI-#11 Water Based Epoxy Primer

VFI-#11 is a general purpose, two component, water based, epoxy primer. It provides excellent adhesion and high strength to most metal, single-ply, concrete, wood, mod bit and BUR surfaces.

This primer can also be used to fill small pits and holes to create a level surface and promote a more even flow of roof coatings.



Contains 4.5 gallons



Contains 0.5 gallons

VFI-1007 Polyurethane Sealer/Primer

VFI-1007 is a single component, solvent based, polyurethane sealer/primer. It can be applied directly to concrete, and is used as a tie coat primer when applying a polyurethane coating over an existing coating. VFI-1007 is intended to be applied to concrete, wood, fiberglass and steel.



VFI-1009 CLEANING CONCENTRATE

VFI-1009 Cleaning Concentrate is a highly effective cleaning agent that, when combined with water, penetrates the existing coating or substrate and allows contaminants to be flushed from the surface.

Formulated with penetrants from wetting agents and surfactants found in certain organic compounds, VFI-1009 performs at a very high level, with cleaning and pore penetrating capabilities far exceeding most products available today. VFI-1009 is non-toxic and leaves no pollutants or contaminating by-products to damage the environment.



PRODUCT INFORMATION

VFI-Primers	VFI-#11	VFI-1007
Color	Salmon	Translucent Black
Viscosity	N/A	50-100 cps
Tensile Strength	N/A	380 psi
Solids	Weight - 60% Volume - 42.5%	Weight - 30.2% Volume - 26.16%
Flash point	N/A	81°F
Liquid Material Density & Specific Gravity	"A" Side - 12.27 lbs./gal (SG 1.473 g/ml) "B" Side - 7.86 lbs./gal (SG 0.945 g/ml)	7.69 lbs./gal (SG 0.958 g/ml)

For more information, contact us today at **800-307-9218**

www.volatilefree.com



This information and technical advice provided herein are believed to be reliable and accurate to the best knowledge of Volatile Free, Inc., As based on tests and should serve only as a recommendation. As the manufacturer, Volatile Free, Inc makes no representations or warranties of any kind, expressed, implied or statutory, including but not limited to all implied warranties of merchantability or fitness for use or a particular purpose, or any other matter with respect to this product. Volatile Free, Inc makes no representations or warranties as to the results of the use of the product and assumes no obligation or liability in connection therewith. Volatile Free, Inc is not liable for any special, exemplary, punitive, incidental or consequential damages of any sort or kind from use of this product. The information provided herein is subject to change at any time without notice. Information changes may include, but are not limited to, commercial and technical changes, changes in pricing, physical characteristics and packaging.