



VFI®-695 Silicone Waterproofing Sealant

VFI®-695 Silicone Waterproofing Sealant is a water repelling formulation providing a durable subsurface barrier. Water based silicone technology provides the benefits of silicone chemistry's chemical resistances to water and oil, while still providing a low VOC. VFI-695 was made to protect masonry products without leaving a visible residue affecting finished appearances.

→ Technical Usage

VFI®-695 Silicone Waterproofing Sealant has been used in the following applications and may be used in many more applications. Contact Volatile Free, Inc. for more information on any specific applications.

- Above Grade Waterproofing

→ Color

Standard color is clear and non-visible.

→ UV Stability

N/A

→ Coverage/Thickness Requirement

See VFI specifications for specific coverage information or contact Volatile Free, Inc. for additional coverage/thickness requirements.

→ Storage Stability/Shelf Life

12 month shelf life from date of manufacture when stored and sealed in unopened containers between 40°F - 75°F. Water based products must be protected from freezing. Material should be brought to a minimum temperature of 65°F before use.

→ Equipment

VFI-695 Silicone Waterproofing Sealant may be applied by single component sprayer, roller, or brush. Contact Volatile Free, Inc. for more information on any specific equipment questions and requirements.

→ Surface Preparation

Surface preparation depends on application and substrate being coated. All surfaces should be cleaned, prepped, dry and free of any oils, dirt or films that could affect the product adhesion. Contact Volatile Free, Inc. with any additional questions.

→ Mixing

Mixing until uniform is required on all material before use. Mix times may vary depending on volume and mixing method. Please contact Volatile Free, Inc. for more information on any specific mixing questions and requirements.

→ Material Application

Material can be applied between 50°F - 120°F and the temperature must remain above 40°F until full cure. Apply only when rain or other moisture contamination will not be present before fully cured. Standard application rate is 1 gallon per 100 square feet. The time between subsequent coats should not exceed 48 hours or the material will block any additional applications. Material cure time will vary with temperature.

→ Primers

N/A

→ Cleanup Solvent

Preferred cleanup method is water. Please contact Volatile Free, Inc. for more information on cleanup of equipment and tools.

→ Thinning








Do not thin prior to application.

→ Precautions

See Safety Data Sheet for complete safety data. Do not add any foreign material to this product. Avoid prolonged breathing of vapors and prolonged or repeated skin contact. Use only with adequate ventilation.

VFI®-695 SILICONE WATERPROOFING SEALANT

Application Method

 SPRAY	 QWIK SPRAY	 BRUSH	 TROWEL	 ROLLER	 INJECTABLE	 POUR
X	-	X	-	X	-	-

Liquid Properties

Solids by Weight	7%
Solids by Volume	7%
Liquid Density	8.19 lbs/gal
Specific Gravity	0.98 g/mL
Viscosity	5 cps
Flash Point	>200°F

Packaging



5 GALLON 1 GALLON

 VOLATILE FREE, INC.

19500 JANACEK COURT | BROOKFIELD, WI 53045 | (262) 787-0400 | TOLL-FREE (800) 307-9218 | FAX (262) 787-0500 | INFO@VOLATILEFREE.COM

This information and technical advice provided herein are believed to be reliable and accurate to the best knowledge of Volatile Free, Inc., As based on tests and should serve only as a recommendation. As the manufacturer, Volatile Free, Inc makes no representations or warranties of any kind, expressed, implied or statutory, including but not limited to all implied warranties of merchantability or fitness for use or a particular purpose, or any other matter with respect to this product. Volatile Free, Inc makes no representations or warranties as to the results of the use of the product and assumes no obligation or liability in connection therewith. Volatile Free, Inc is not liable for any special, exemplary, punitive, incidental or consequential damages of any sort or kind from use of this product. The information provided herein is subject to change at any time without notice. Information changes may include, but are not limited to, commercial and technical changes, changes in pricing, physical characteristics and packaging.